

Mobile air conditioners / Technical data

Indoor unit		AM12HEIA4	
Power supply		Ph/V/Hz	1 / 220~240 V / 50 Hz
Cooling	Rated capacity	W	3400
	EER	W/W	2.6
	Rated power input	W	1,300
Heating	Rated capacity	W	2,700
	COP	W/W	2.7
	Rated power input	W	1K
	Rated current	A	4.60
Maximum power input		W	1,450
Maximum current		A	8.00
Starting current		A	/
Plug type		A	16
Compressor	Model		DSM215V2UDZ
	Type		Rotary
	Brand		GMCC
	Capacity	Btu/h	10,918
	Power input	W	985
Internal fan motor	Model		YDK15-6
	Brand		WELLING
	Power input	W	52.5
	Capacitor	μF	1.5
Internal airflow	Speed (high/mid/low)	rpm	630/570/490
	(high/mid/low)	m³/h	390/360/330
Sound power level	(high/mid/low)	dB(A)	64/63.5/63
External fan motor	Model		YDK45-4
	Brand		WELLING
	Power input	W	119
	Capacitor	μF	3.5
External airflow	Speed	rpm	1,130
		m³/h	550
Unit dimensions	(W x H x D)	mm	476 x 710 x 385
Packaging dimensions	(W x H x D)	mm	545 x 885 x 435
Net/gross weight		kg	33.5/38.5
Refrigerant			R290

