

2,0 kW

2,5 kW

3,5 kW

5,0 kW

6,8 kW


# PEARL



Standard YR-HE



Silence



Self Clean



Wi-Fi control integrated



UVC Sterilisation



Easy Installation



Coanda Plus

- Low noise level
- Self-Clean (Only Dual)
- Wi-Fi control integrated
- UVC Sterilisation
- Easy installation
- Coanda plus airflow



Indoor Unit	Model		AS20PBAHRA	AS25PBAHRA	AS35PBAHRA	AS50PDAHRA	AS68PDAHRA
<b>Performance data</b>							
Output power - COOLING	nom (min-max)	kW	2,00	2,60 (0,80-3,00)	3,20 (0,80-3,60)	5,00 (1,30-5,80)	6,80 (2,20-8,50)
Output power - HEATING	nom (min-max)	kW	2,50	2,80 (0,80-3,20)	3,40 (0,80-4,20)	5,20 (1,40-6,00)	6,80 (2,40-9,50)
Power supply		Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
Interconnection cable			4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0
Treated air volume	H	m3/h	550	550	600	900	1100
<b>Indoor Unit</b>							
High sound power - COOLING		dB	54	54	56	57	62
High sound power - HEATING		dB	54	54	56	57	62
Sound pressure - COOLING		dB(A)	37/32/28/18	37/32/28/18	37/33/29/19	44/40/35/28	47/45/37/29
Sound pressure - HEATING		dB(A)	37/32/28/18	37/32/28/18	37/33/29/19	44/40/35/28	47/45/37/29
Net dimensions	WxDxH	mm	805x200x290	805x200x290	805x200x290	975x220x320	975x220x320
Packaging dimensions	WxDxH	mm	874x270x363	874x270x363	874x270x363	1050x301x397	1050x301x397
Net/gross weight		kg	8,3/10,5	8,3/10,5	8,3/10,5	11,6/14,4	11,6/14,4
<b>Installation data</b>							
Liquid pipe	∅	mm	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)
Gas pipe	∅	mm	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	12,70 (1/2)
<b>Control</b>							
Standard	Remote control		YR-HE	YR-HE	YR-HE	YR-HE	YR-HE

AS20 - AS25 - AS35



AS50 - AS68

